

Moving from UI to a
Presentation Layer

BUSINESS
MAKING
PROGRESS

Peter Judge
pjudge@progress.com





User Interface is the implementation of the intended User Experience in terms of page layout, page transitions and page control elements ^[1]

Presentation layer is the design and implementation of the code and other resources that provide that UI


[1] peterchen on Stackoverflow.com: "Difference between presentation layer and user-interface"
<http://stackoverflow.com/questions/2907024/difference-between-presentation-layer-and-user-interface/2925053#2925053>

What's the difference? Aren't they the same thing?

Differently put, UI is what you see, PL is what shows it to you.

```
for each Customer:  
  display CustNum  
  with frame f1Cust 1 down.  
end.
```

How many of you recognise this? Most of you 😊



You can argue that FOR EACH CUSTOMER is a presentation layer in itself. There's code, there's interaction with a human or 2. All set, right?

So I guess to clarify what I mean by presentation layer in the context of this session. Today we'll look a little deeper into the **design** aspect of the presentation layer, although we'll do so largely through code.

```
for each customer:  
  displ custnum  
  with frame fCust 1 down.  
end.
```

What do we have here? A way to

... get data

... show data

... process inputs

It's quite a powerful few lines of code ...

This code contains all of the concepts and code that we need/want to work on

It gets data, shows data and handles user input.

The Beginning: A Very Good Place To Start

BUSINESS
MAKING
PROGRESS

```
for each customer:  
  displ custnum  
  with frame fCust 1 down.  
  
end.
```

What do we have here? A way to

```
... get data  
  
... show data  
  
... process inputs
```

© 2011 Progress Software Corporation. All rights reserved.

No way to process inputs? Think about the 'press spacebar to continue' message .

This is not very nice code for a number of reasons

1. Direct DB access
2. No way to intercept user input in ABL

The Beginning: A Very Good Place To Start

```
for each customer:  
  displ custnum  
  with frame fCust 1 down.
```

```
end.
```

What do we have here? A way to

```
... get data
```

```
... show data
```

```
... process inputs
```

No way to process inputs? Think about the 'press spacebar to continue' message .

This is not very nice code for a number of reasons

1. Direct DB access
2. No way to intercept user input in ABL

The Beginning: A Very Good Place To Start

```
for each customer:  
  displ custnum  
  with frame fCust 1 down.  
end.
```

What do we have here? A way to

... get data

... show data

... process inputs

No way to process inputs? Think about the 'press spacebar to continue' message .

This is not very nice code for a number of reasons

1. Direct DB access
2. No way to intercept user input in ABL

An Important Improvement

```
define temp-table ttCustomer no-undo  
  like Customer.
```

```
run GetCustomers  
  (input cWhereClause,  
   output temp-table ttCustomer).
```

```
for each ttCustomer:  
  displ custnum  
  with frame fCust 1 down.  
end.
```

© 2011 Progress Software Corporation. All rights reserved.

Much better.

Having something like `GetCustomers()` is very important since it allows us to populate `ttCustomer` any way we want to. We can filter, sort, slice and dish, mashup and futz with our data any way we want, WITHOUT having to change the display. We have a contract (of sorts) contained in the temp-table definition, and if we mess things up – like remove the `CustNum` field – the compiler lets us know all about it.

Direct DB connection broken in this program, but still UI issues remain. Still local.

A Further Modest Improvement

Now with AppServer!

```
define temp-table ttCustomer no-undo
  field CustNum as integer
  /* fields */.
hAppServer
  :connect("-AppService asPugChallenge11").

run GetCustomers on hAppServer
  (input cWhereClause,
   output temp-table ttCustomer).

for each ttCustomer:
  displ custnum
  with frame fCust 1 down.
end.
```

10 © 2011 Progress Software Corporation. All rights reserved.

Notice that we've changed the temp-table definition to define the fields, rather than using "Like Customer". We've now completely broken the dependency on the database in our UI code. `getCustomers()` obviously still needs to know where to get the data from, but the UI has no clue.

Ok, now we have a decent starting point. We run on the AppServer, which means we get performance benefits: more machine, typically. We can also ask for a subset of data by passing filter criteria.

This is a very simple starting point, but it's intended to illustrate the concepts and separate concerns that we're dealing with.



Time to look at real* code

* relatively real-ish, at any rate

Client/customerwin.w

```
customerwin.w
GetCustomerData on hAppServer
define query on ttCustomer
query navigation
define UI (frames)
define buttons & 'on choose' triggers
perform ui logic
hold things together
```

Let's put this in terms of our earlier categorisations

```
customer_eventhandler.p
```

```
perform ui logic  
hold things together
```

```
customer_clientdata.p
```

```
getCustomerData on hAppServer  
define query on ttCustomer  
query navigation etc
```


```
customer_abl_gui.p
```

```
customer_net_gui.cls
```

```
customer_web_ui.p
```

```
define UI (frames, controls, pages)  
define buttons / links & 'on choose' triggers
```

Now each action has it's own program / component



Tying the pieces together

14 © 2011 Progress Software Corporation. All rights reserved.

Client/customerwin.w

Presentation Layer Design

BUSINESS
MAKING
PROGRESS

Always working with 3 parts

1. Something to hold data
2. Something to show the data to a user
3. Something to receive the user's actions

We also need something to hold everything together

- Multiple designs that combine these 3 concepts
 - MVC (model-view-controller)
 - PAC (presentation-abstraction-control)
 - MVP (model-view-presenter)
 - MVVM (model-view-view-model)

15 © 2011 Progress Software Corporation. All rights reserved.

Data: Not a DAO but a client-side proxy of business entity.
Ok so more like 4 parts.


There are many named designs - or patterns - for implementing this stuff. MVC, MVP, ...
Note that they all have 3 parts. Even MVVM is really only 3 parts.

MVC – controller takes user input directly

PAC – controller takes user input directly

MVP – lets view take some input

MVVM – view-model is effectively a controller. Introduced for Silverlight



The directions and strength of the connections also differentiate the patterns. Conceptually, they're all quite similar, and hence a lot of confusion about what differentiates them. I'll try to explain.

Model-View-ViewModel (MVVM)

Derivative of PresentationModel :

“ The essence of a *Presentation Model* is of a fully self-contained class that represents all the data and behavior of the UI window, but without any of the controls used to render that UI on the screen^[1]

“ MVVM a specialization of this the more general PM pattern, tailor-made for the WPF and Silverlight platforms^[2]

Model and View are same as for MVP/MVC


1. Martin Fowler, Presentation Model (<http://martinfowler.com/aaajDex/PresentationModel.html>)
2. Josh Smith, WPF Apps With The Model-View-ViewModel Design Pattern
<http://msdn.microsoft.com/en-us/magazine/ee419663.aspx>

PresentationModel/ViewModel means that even without seeing the UI we know what the UI looks like (as it were).

WVVM is pretty MS-specific (XAML etc).



What does OERA use?




Using Model-View-Presenter (you might have seen that coming :)


Allows Views to do some work – necessary with multiple UI techs (.cls, .p etc)
 Supervising Presenter Variant/Pattern allows View / Model communication

Fits well within OpenEdge Reference Architecture
 Though can be used outside OERA

While the decision of design patterns to use should be technology-agnostic as far as possible, the ABL's heritage of providing strong or tight data binding constructs in the language – going back to the DISPLAY and UPDATE statements and continued in the OpenEdge ProBindingSource object – mean that the Supervising Presenter is a pattern well-suited to ABL applications' presentation layers.



As you'd expect from the title of this talk, it fits into Presentation Layer. Talks to Business Components, Common Infrastructure



Note that the Model becomes a conduit to the data layer (business components). So in OERA the Model typically talks to a Business Entity

```
customer_presenter.p      customer_eventhandler.p
perform ui logic
hold things together
```

```
customer_model.p         customer_clientdata.p
getCustomerData on hAppServer
define query on ttCustomer
query navigation etc
```

```
customer_view_window.p   customer_abl_gui.p
customer_view_form.p     customer_net_gui.cls
customer_view_page.p     customer_web_ui.p
define UI (frames, controls, pages)
define buttons / links & 'on choose' triggers
```

Now each action has it's own program / component

Tying it back to the code

```
customer_presenter.p      customer_eventhandler.p
perform ui logic
hold things together

customer_sdo_model.p
customer_json_model.p
customer_db_model.p
customer_be_model.p      customer_clientdata.p
getCustomerData on hAppServer
define query on ttCustomer
query navigation etc


customer_view_window.p    customer_abl_gui.p
define UI (frames, controls, pages)
define buttons / links & 'on choose' triggers
```

24 © 2011 Progress Software Corporation. All rights reserved.

This pattern lets us swap out the model-side code for different models, without the presenter/views caring

Summary

- Reusable, consistent logic across UI technologies
 - We already knew about business logic reuse
 - Now have reusable UI logic
- Better separation of concerns
 - View does UI
 - Model does Data
 - Presenter does Thinking
- Supports incremental migration
- Easier testing, clearer points of failure



25 © 2011 Progress Software Corporation. All rights reserved.

Separation of concerns:

- View ... easier to build new Uis
- Means that we can swap out things like Models too, without affecting the other components.

Testing: Maybe fewer bugs. More like fewer places for bugs to appear

Further Reading

- OERI Model View Presenter Architecture
<http://communities.progress.com/pcom/docs/DOC-109108>
- AutoEdge|TheFactory
http://communities.progress.com/pcom/community/psdn_opensedge/architecture/autoedgethefactory
- OERA Presentation Layer
<http://communities.progress.com/pcom/docs/DOC-34978>
- MVC <http://heim.ifi.uio.no/~trygver/themes/mvc/mvc-index.html>
- Portland Pattern Repository
MVC <http://c2.com/cgi/wiki?ModelViewController>
MVP <http://c2.com/cgi/wiki?ModelViewPresenter>
- MVVM
 - <http://msdn.microsoft.com/en-us/magazine/dd419663.aspx>
 - <http://www.nikhilk.net/Silverlight-View-Model-Pattern.aspx>
 - http://en.wikipedia.org/wiki/Model_View_ViewModel
 - <http://www.nikhilk.net/View-View-Model-Interaction.aspx>
- "Build your own CAB" (nice overview of many topics)
<http://codebetter.com/jeremymiller/2007/07/26/the-build-your-own-cab-series-table-of-contents/>

PROGRESS
software



BUSINESS
MAKING
PROGRESS

Peter Judge

pjudge@progress.com



BUSINESS
MAKING
PROGRESS™

PROGRESS
REVOLUTION

Sept. 19 – 22, 2011
Boston Westin Waterfront Hotel
and Boston Convention & Exhibition Center

